



## Technical Data Sheet\*

# CSW 4075 White Petrolatum

*\*Manufactured products shall conform to specifications. Revision Date: 3/12/2007*

Test Description	Test Method	Min.	Max.	Typical
MELT POINT, DROP °F(°C)	ASTM D-127	130 (54.4)	160 (71.1)	145 (62.8)
CONE PENETRATION, dmm @ 77°F	ASTM D-937	---	---	110
KINEMATIC VISCOSITY, cSt @ 210° F	ASTM D-445	10.0	17.0	14.0
ASTM COLOR	ASTM D-6045	---	0.5	---
FDA STATUS	This product is not intended for contact with food.			

### WARRANTY DISCLAIMER STATEMENT

Please be advised that there are no warranties, representations or conditions, expressed or implied, of any kind, including, but not limited to, merchantability or fitness for a particular purpose made by CLARUS SPECIALTY PRODUCTS, LLC (Hereafter "CLARUS") or its officers, employees or affiliates, in connection with the sale of the products described in this bulletin. The information contained in this document is based solely on tests, which are believed to be reliable. As actual conditions of use may vary and are beyond the control of CLARUS, the product's specified characteristics cannot be guaranteed and are offered solely for the buyer's evaluation and verification. Accordingly, the purchaser and each user assume all risks and liability connected to their specific use of such products. Nothing contained herein is to be construed as permission, recommendation or inducement by CLARUS or its officers, employees or affiliates, to use any product or process so as to infringe or conflict with any patent. Further, it is the user's obligation to utilize this material in full compliance with all required health, safety and environmental regulations. CLARUS recommends that the Material Safety Data Sheet for this product be consulted prior to handling and use.