raybo TECHNICAL BULLETIN

Raybo Chemical Company

TELEPHONE: 304-525-5171

Raybo 75 ProtectR

FEATURES

SYSTEM

COMMENTS

USAGE (%)

Highly

Compatible

Emulsion Water Reducible Complementary

1 - 2%

Resists Corrosion

Solvent

to Corrosion Resistant

Total Weight

Undercutting

Pigments

PERFORMANCE

Raybo 75 is a hydrophobic complex formulated to provide long term corrosion protection to emulsion, water reducible, and solvent based coatings. Raybo 75 chemiadsorbs to steel providing increased adhesion, preventing undercutting, and providing a hydrophobic barrier to resist moisture attack.

In aggressive water systems, use a flash rust inhibitor in addition to the Raybo 75.

This provides protection during the critical drying cycle.

ADVANTAGES

Provides corrosion protection in a liquid form without the need for anticorrosive

pigments.

RECOMMENDATIONS

1-2% of Total Weight

PHYSICAL DATA**

Weight/Gallon

8.14

Consistency

Thick Liquid

Melting Point

<0°F

CONTAINER SIZES

North American: 5 gal. pail*, 55 gal. drum, and bulk.

Global Zones: 5 gal. pail*, 55 gal. drum.

The information and data stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty either expressed or implied, is made or intended. Use by customer should be based upon its own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.

Performance Additives Department

Huntington, WV 25721 Tel.: 304-525-5171 Fax: 304-525-2921

US Marketing Division Raybo Chemical Company Huntington, WV 25721 Tel.: 304-525-5172

Fax: 304-525-2921

Exclusive Export Management Company W.R. Magnus, Inc. Tel.: 312-263-6124

Email: rwmagnus@cocexport.com

Global Dist. Zones Representatives in 31 Countries

^{*} One gallon containers available upon request.

^{**} Typical Properties; not sales specifications.