



TECHNICAL BULLETIN

Raybo Chemical Company

TELEPHONE: 304-525-5171

RAYBO 90 - NoRust NF

Flash Rust and In-Can Corrosion Protection

REFERENCE	FEATURES	SYSTEM	COMMENTS	USAGE (%)	REFERENCE
	Nitrite Free Eliminates Flash Rust and In-Can Corrosion	Water	Corrosion Inhibitor for "Green Formulations"	0.5-2% of Total Weight	

PERFORMANCE

RAYBO 90 NoRust NF provides superb flash rust and in-can corrosion protection for nitrite sensitive markets.

ADVANTAGES

- Nitrite Free
- Eliminates flash rust in direct-to-metal applications
- Vapor phase in-can protection
- Protects micro-cracked lined containers
- Flash rust protection in a wide variety of resin systems

RECOMMENDATIONS

Flash Rust Control 1-2% of total weight
 Corrosion Prevention for unlined containers 1-2% total weight
 Lined containers 0.5-1% total weight
 Post addition recommended
 Raybo 90 is most effective at pH above 8.5

PHYSICAL DATA**

Weight/Gallon 8.7 lbs.
 pH >10
 Appearance Straw-colored Liquid
 Viscosity 15 sec. #2 Zahn Cup

CONTAINER SIZES

North American: 5 gal. pail*, 55 gal. drum, and bulk.
 Global Zones: 5 gal. pail*, 55 gal. drum.

* One gallon containers available upon request.

** Typical Properties; not sales specifications.

The information and data stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty either expressed or implied, is made or intended. Use by customer should be based upon its own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.

 Performance Additives
 Department
 Huntington, WV 25721
 Tel.: 304-525-5171
 Fax: 304-525-2921

U.S. Marketing Division
 Raybo Chemical Company
 Huntington, WV 25721
 Tel.: 304-525-5172
 Fax: 304-525-2921

 Exclusive Export
 Management Company
 W. R. Mangus, Inc.
 Tel.: 312-263-6124
 Email: rwmagnus@cocexport.com



Global Dist. Zones:
 Representatives in
 31 Countries